# Model 1200L



## 1200 lbs Single Magnetic Lock with Status LED

## **Specifications**

- 1200 lbs holding force
- Magnet size: 10-1/2" L x 2-7/8" H x 1-1/2" W
- Armature size: 7-3/8" L x 2-3/8" H x 9/16" W
- Operates on 12 or 24 VDC, selectable
- Low current draw: 400 mA at 12 VDC, 200 mA at 24 VDC
- Operating temperature: +14 to +131F [-10 to +55C]

#### **Features**

- Instant release, no hysteresis
- Red status LED
- Self drilling TEC screws
- Built-in arc suppression
- E-Z mount system, no special tools required
- Non-aluminum parts are plated to resist corrosion

- Can be used with any access control system
- Limited lifetime warranty

### **Options**

- Clear anodized (US28) finish standard
- Duranodic (US40) finish available
- Dress covers in polished chrome and brass are available

## Certifications & Listings

- UL 294 listed
- UL 10C fire rated
- CAN/ULC-S104 fire door conformant
- ULC-S527 listed
- UL 864 listed

#### **Models**

#### 1200L

1200 lbs Single Door Magnetic Lock with status LED, 12 or 24 VDC, UL 10C and Canadian UL Listed

#### **1200LDURO**

1200 lbs Single Door Magnetic Lock with status, LED, 12 or 24 VDC, US 40 Duranodic Finish, UL 10C and Canadian UL Listed



