

ELK

PRODUCTS



All Weather Door & Gate



Window & Shock



Wall Mounted Motion



Glass Break



1 Button Panic

4 Button Remote

319.5 MHZ WIRELESS SENSORS



Versatile

319.5 MHz Frequency

- Ideal for servicing existing Interlogix systems in need of replacement sensors
- Compatible with many popular systems including ELK's E27 and M1 Controls



Reliable

MaxOut™ Technology

- Maximum RF power output
- Increased coverage
- Extended battery life
- Superior performance



Economical

Exceptional Quality, Low Cost

- Competitively priced
- Built the ELK way for years of reliable service
- Uses common batteries for convenience and lower maintenance costs



Mini Door & Window



Recessed Door



360° Motion



Heat Rate-of-Rise & Fixed Temp



Heavy Duty Panic

elkproducts.com/319wireless



All Weather Door & Gate

ELK-319DG

- Designed for outdoor use on swing gates or doors
- Supports connection of external contact
- Uses two CR2032 for maximum life and range



Mini Door & Window

ELK-319DWM

- Small, low profile sensor for doors and windows
- Uses two CR2032 for maximum life and range



Window & Shock

ELK-319WS

- Detects the opening of a window or vibrations made by an intruder attempting to break the window
- Operates from two CR2032 batteries for max range and battery life



Recessed Door

ELK-319DR

- Recess mounted door sensor is virtually invisible when door is closed
- Utilizes a single common & easy to find CR2 battery



360° Motion Detector

ELK-319PIRC

- 360° detection area of 14-40 feet.
- Designed for ceiling mount applications
- Uses two CR2032 for maximum life and range



Wall Mounted Motion Detector

ELK-319PIRW

- Detection area of 40 feet
- Designed for wall mount installations
- Uses one CR123A for maximum life and range



4 Button Key Chain Remote

ELK-319KF4

- Can be used to arm and disarm the alarm system
- Two additional buttons can be utilized as panic alarm or other functions



Single Button Remote Panic

ELK-319KF1

- Can be used for a police, medical, or auxiliary panic alarm activation
- Simple one button operation



Heavy Duty Panic Button

ELK-319PB1

- Can be used for a police, medical, or auxiliary panic alarm activation
- Includes belt clip, lanyard clip and wall mount bracket



Glass Break Detector

ELK-319GB

- Detects sound patterns of breaking glass
- Range 20 ft max; selectable sensitivity
- Uses two CR123 for maximum life and range



Heat Rate-of-Rise and Fixed Temperature

ELK-319HRR

- Selectable setpoint of either 135°F or 200°F
- Rate-of-rise detection of 12°F

319.5 MHz Wireless Receiver for E27

ELK-AERF3

- Supports ELK's 319 Series wireless products
- Adds up to 128 wireless zones to E27 Alarm Engine

319.5 MHz Wireless Receiver for M1

ELK-M1XRF319

- Supports ELK's 319 Series wireless products
- Adds up to 144 wireless zones to M1 Controls