

# 22AWG 4C STRAND CMR

Part Number: BC-224STRCMR



## Listings

Listings c(ETL)us UL Standard 13 and 42 444, TIA/EIA-568-C.2 NEC Articles 800 CMR

## Construction

Conductor	22 AWG bare copper
Stranding	7/30
Insulation Material	PE
Nom. Insulation Thickness	0.009"
Insulated Conductor Diameter	0.047"
Number of Conductors	4
Nom. Lay Length	4.5"
Jacket Material	PVC
Jacket Thickness	0.015"
Nom. Overall Cable Diameter	0.150"
Approximate Cable Weight (lbs./Kft.)	15
Flame Rating	UL 1666 vertical tray flame test
Rip Cord	No

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	16.19 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	21 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Black   Red   White   Green
Jacket Color	Gray
Legend (Surface Ink Print)	****/**** comCables 224STR 22AWG 4CTYPE CMR c(ETL)us 5000838 DC 1014 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9