


HD-TVI Multi-Format Intensifier® Corner Mount Camera

CVC605CMT1 3.6mm fixed board lens, stainless steel housing

Features

- Full HD resolution over coax (HD-TVI)
- Supports up to 1080p @ 30fps
- Perfect for elevators, hallways, etc.
- Full OSD operation via UTC (TVI)
- Supports HD-TVI, CVI, AHD, 960H
- Signal distance up to 1600 ft. (depending on coax quality)*
- 12VDC operation (power supply not included)
- 5 year warranty



Camera Specifications

Image Sensor1/2.9" 2MP CMOS
 Resolution.....1920 x 1080
 Minimum Illumination.....0.001 lux
 Scanning System.....Progressive
 S/N Ratio>52dB
 Video OutputHD-TVI, CVI, AHD, 960H
 Day/Night.....Auto / Color / BW / EXT
 White BalanceATW
 Brightness.....0 - 20
 DWDROff

Camera Specifications (continued)

Sens upOn
 Backlight Compensation.....Off
 Communication.....UTC

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Operating & Unit Specifications

Power Supply12VDC power supply
 (power supply not included)
 Power Consumption12VDC, 70mA
 Operating Temperature.....14° F – 122° F
 Operating Humidity.....20% – 80% RH
 Storage Temperature.....-22° F – 140° F
 Dimensions.....9.3" (W) x 6.7" (H)
 Weight1.4 lbs.

Optional Accessories



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver

*To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/23/22