



333 Bayview Avenue  
 Amityville, New York 11701  
 For Sales and Repairs, (800) 645-9445  
 For Technical Service, (800) 645-9440  
 Publicly traded on NASDAQ Symbol: NSSC

© NAPCO 2010

# FWC-FSLC-PROG2 Programming Tool DATA SHEET

WI1925 09/10

## ORDERING INFORMATION

The **FWC-FSLC-PROG2** is a hand held programming tool; it is not a "device" that is wired to the GEMC-FW-SLC. The **FWC-FSLC-PROG2** is used to manually confirm or reset a 3-digit "internal device address" number programmed within each device. These three numbers (001-126) are used to identify the device to the system. The **FWC-FSLC-PROG2** is powered by one 9V (PP3) battery.

For more information, see WI1738.

## COMPATIBLE DEVICES

FWC-FSLC-PROG2 is designed for use with the following products:

**FWC-FSLC-SMK** - Analog Photoelectric Supervised Smoke Sensor Detector. Note: The GEMC-FW-SLC employs drift compensation for all FWC-FSLC-SMK detectors on the loop. For more information, see WI1709.

**FWC-FSLC-HEAT** - Low profile Heat Sensor with adjustable threshold temperature, 0°F-190°F (default = 135°F). For more information, see WI1709.

**FWC-FSLC-DUCT** - Easy-Install Photoelectric Analog Duct Detector. Detects and limits the spread of smoke throughout building HVAC ducts. For more information,

see WI1711.

**FWC-FSLC-EZM2** - Dual Input Monitor Module. Monitors Fire alarm and other supervisory devices. Fits into a standard 4" square or double gang electrical back box. For more information, see WI1712.

**FWC-FSLC-EZM1** - Fast Response Contact Module. Single-input contact monitors dry contact alarm initiating devices. For more information, see WI1713.

**FWC-FSLC-CZM** - Conventional Zone Module. Allows the panel to interface and monitor dry contacts such as pull stations and compatible two-wire conventional smoke detectors. Status conditions are reported as normal, open or alarm. Maximum 8 allowed per GEMC-FW-SLC board. For more information, see WI1714.

**FWC-FSLC-RM2** - (Output device) Dual Relay Module provides two independently configurable Form C contacts per address, Contacts rated 1.0A @ 30VDC or 0.5A @ 125VAC. For more information, see WI1715.

**FWC-FSLC-SOM1** - (Output device) Supervised Output Module, provides a Class B Individual Circuit rated for 2A/30VDC. For more information, see WI1717.

## Components

