

iBridge Video™: Affordable Professional Hi-Res. Remote Video



High HD resolution remote video online or on a smart device up to 20 frames per second at HD res (1280 x 960).



iBridge Video™: Wi-Fi IP Indoor & Outdoor Cameras - Use alone or integrate with iBridge Connected Home App

WiFi Camera Features:



- › Put video accounts online in as little as 10 minutes
- › **Upsell your residential & small business alarm accounts on very affordable video for incremental RMR**
- › High HD resolution remote video up to 20 frames per second at HD res (1280 x 960)
- › **Built in 32GB Onboard HD video storage**, for up to 7 days, viewable from App or online.
- › Choice of new cameras, including outdoor dome model, all including one year of subscriber service.
- › **New outdoor dome camera with choice of WiFi or POE connectivity and mounting options** for wall, ceiling or eave. Ingress protection & vandal resistance, IP67, IK10.
- › No dedicated wireless access point required
- › Easiest 802.11 camera enrollment: Scan QR code, name camera and enroll in seconds
- › **Free Apps** for standalone remote video or as part of iBridge Connected Home (including integral review of optional IVR archived video) on iTunes® and GooglePlay®
- › Cameras support full duplex, **2-way audio through App - Talk to premises live** (excludes outdoor dome camera model).

Or, Use Your Own Analog Cameras with Single Channel Gateway option.

Plug in CAT5 cable into router and simply enroll into network converting analog data into high-quality IP.

INTERNET VIDEO RECORDER OPTION

Continuously record and store 90 days of video from up to six cameras with model **IVR-IT** for 1 Terrabyte of storage or model **IVR-4T** for 4 Terrabytes. All viewable online or via iBridge Video App (right).



Easy remote video app for use on smart devices or online, lets accounts see what they're missing.

iBridge Video™ Wi-Fi IP Indoor & Outdoor Cameras for Remote Video



	WiFi Fixed Camera	WiFi P/T Camera	WiFi Mini Dome Camera
Model	ISV2-CAM	ISV2-PT	ISV2-DOME
WiFi IEEE 802.11 b/g/n	2.4GHz	2.4GHz	2.4GHz
Hi-Def. Image Sensor	1/3" 1.3MP CMOS	1/3" 1.3MP CMOS	1/3" 1.3MP CMOS
App for Standalone Remote Video	New iBridge® Video App (iTunes/GooglePlay)	New iBridge® Video App (iTunes/GooglePlay)	New iBridge® Video App (iTunes/GooglePlay)
App for Integrated Video as a part of Connected Home	iBridge® App (iTunes/GooglePlay)	iBridge® App (iTunes/GooglePlay)	iBridge® App (iTunes/GooglePlay)
iBridge Messenger, Video Notifications, MMS	MMS live pre/post video clips sent as Push Notifications to mobile App	MMS live pre/post video clips sent as Push Notifications to mobile App	MMS live pre/post video clips sent as Push Notifications to mobile App
Special Features	PIR w/ 19.7' Range		PoE-Ready
Lens	2.8mm/F2.2	3.6mm/F2.1	2.8mm/F2.0
FOV-H	92°	72°	92°
Day/Night	Auto ICR	Auto ICR	DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
Wide Dynamic Range	DWDR	DWDR	DWDR
Night Vision, Max IR Distance	32.8' (10m)	32.8' (10m)	98.4' (30m)
Video Compression	H.264	H.264	H.264
Max. Resolution	1.3MP (1280x960)	1.3MP (1280x960)	1.3MP (1280x960)
Frame Rate, Max.	25/30fps@1.3MP	30fps@1.3MP	30fps@1.3MP
Pixel-Based Motion Detection	Yes	Yes	Yes
Pan/Tilt/Rotation	Pan 0° -360°; Tilt 0°, 90°; Rotation 0-360° (fixed)	Pan 0°-355°; Tilt 0°- 90°	Pan 0° -355°; Tilt 0°- 90° (fixed)
Pan/Tilt/Range	n/a	Pan 0° -355°; Tilt 0°- 90°; 25 preset	n/a
Audio In/Out, 2-Way thru App	True 2-Way, Built in Mic/Speaker	True 2-Way, Built in Mic/Speaker	n/a
7 Day Memory, Onboard	32GB	32GB	32GB
Color	White/Gray	White/Smoke	White/Clear
Mounting (std hardware incld)	Shelf/Wall	Shelf/Wall	Wall/Ceiling/Eave
Optional Mounting Accessories			Optional Mounting Bracket ISV2-or Optional Waterproof Round Junction Box
Other Available Accessories			4-Port or 8-Port PoE Switch
Compliances	CE, UL, FCC	CE, UL, FCC	CE, UL, FCC; IP67, IK10
Operating Temperature	14° ~ 113°F, Less than 95%RH	14° ~ 113°F, Less than 95%RH	120°C to 50°C; 14°F to 122°F
Dimensions , max.	5"H x 3"W x 3.25"	3.7" X 3.7" x 3.7"	4.33" x 3.19"
Power Supply, included	DC 12V	DC 5V2A	DC 12V
Weight	5.5oz	7.76 oz	1.2lbs

Ordering Information for iBridge Video Wireless Cameras & Accessories

ISV2CAM WiFi Hi-Def. Fixed Camera with built-in PIR, true 2-way audio built in mic/speaker and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, fast-connect, up to 20/30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Gray styling, Shelf or wall mount. 5x 3 x 3.25" Includes power supply and mounting hardware. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. subscriber service. (Supports all current wireless routers - no special WAP required.)

ISV2-PT WiFi Hi-Def. Pan/Tilt Camera, true 2-way audio built in mic/speaker and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, Professional grade, fast-connect, up to 30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor; Pan 0-355 degrees and Tilt 0-90 degrees. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Smoke styling, Shelf or wall mount. 3.7 x 3.7 x 3.7". Includes power supply and mounting hardware. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. subscriber service. (Supports all current wireless routers - no special WAP required.)

ISV2-DOME WiFi Hi-Def. Indoor/Outdoor Dome Camera with POE option and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, Ingress & Vandal- Protected Weatherproof camera (IP67, IK10) for wall, ceiling or eave mounting. Professional grade, fast-connect, up to 30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor. Provides subscribers MMS Video Push Notifications on smart mobile devices with 10 second alarm/event alerts. White/Clear styling 4.33 x 3.19". Includes power supply and mounting hardware. Also see optional Mounting Bracket and Round Waterproof Junction Box and optional 4- or 8-Port POE Switch. Use as standalone remote video with iBridge Video App or as part of iBridge Connected Home with iBridge App. Includes 12mos. subscriber service. (Supports all current wireless routers - no special WAP required.)

ISV2-DM MTB Optional Round Junction Box for Dome Camera

ISV2-DM BKT Optional Wall Mounting Bracket for Dome Camera

ISV2-POE-4P 4 Port PoE Switch, optional accessory for ISV2-DOME camera, above. Two-layer industrial POE switch, MAC auto study and aging, MAC address list capacity is 8K. Support IEEE802.3af, IEEE802.3af standard.

ISV2-POE-8P 8 Port PoE Switch, optional accessory for ISV2-DOME camera, as above, but includes 8 ports.

ISEE-IVR-4T/12 Optional Four-Terrabyte Internet Video Recorder, 8 Channels Fully supervised; an ideal replacement for old DVRs, plus a new RMR stream. Provides full time HD 720P (1280x960) recording of up to 4 cameras for at least 180 days with full review and easy search functions H.264/MJPEG video compression, HDMI, VGA display, 1x100M Port Ethernet, also includes USB 2 Ports for backing up video to USB 2.0. DC12V/2A power supply (included). Includes 12mos. subscriber service.

ISEE-IVR-1T/12 Optional One-Terrabyte Internet Video Recorder as above, but HD 720P recording of up to 4 cameras for at least 45 days. Includes 12mos. subscriber service.



333 Bayview Avenue, Amitville, NY 11701
1.800.645.9445 • www.napcosecurity.com