



# 4MP IP Bullet Camera with AI and Audio and Visual Deterrent, NDAA Compliant

## O4BDD1M

2.8-12mm motorized lens, white housing



### Features

- Captures up to 4MP @ 30fps real time
- Built-in speaker with preset and custom sounds provides audio deterrence
- Built-in high-power red and blue lights provides visual deterrence
- IR range: up to 164' (depending on scene reflection)
- True WDR operation
- Micro SD card slot (card not included)
- ONVIF Profile T Compliant
- IP66 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection\*
- Person/Vehicle detection\*
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty
- NDAA Compliant\*\*



### Camera Specifications

|                          |   |
|--------------------------|---|
| Image Sensor             | Progressive scan 1/3" CMOS  |
| Maximum Resolution       | 2592 x 1520 (4MP)   |
| Field of View            | Horizontal: 94.2°~ 29.8°, Vertical: 62.4°-17°, Diagonal: 102°-33.9° |
| Minimum Illumination     | 0.005lux @ F1.6(AGC ON) ; 0 lux @ IR ON                             |
| White Balance            | Auto, Indoor, Outdoor, Manual                                       |
| Compensation             | True WDR (120dB), BLC, HLC  |
| Day/Night                | Smart IR  |
| Electronic Shutter Speed | 1s ~ 1/100000s  |
| DNR                      | 3D DNR  |
| Angle Adjustment         | Pan: 0° ~ 360°; Tilt: 0° ~ 90°; Rotation: 0° ~ 360°                 |

### Video Specifications

|                    |   |
|--------------------|---|
| Main Resolution    | 2592x1520, 2560x1440 2304x1296, 1920x1080, 1280x720, D1, CIF, 480x240 @ 30fps   |
| Substream          | 1280x720, D1, CIF @ 30fps   |
| Third Stream       | D1, CIF, 480x240 @30fps   |
| Compression        | Main stream: H.265+ / H.265 / H.264+ / H.264<br>Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG<br>Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG          |
| Bitrate Control    | VBR, CBR (64Kbps ~ 8Mbps)   |
| Multiple Streaming | 3 streams   |
| Video Settings     | Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror |

### Client Specifications

|                     |  |
|---------------------|--|
| Web Browser Support | Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari |
| PC Application      | SecureGuard® VMS and SecureGuard® CMS                          |
| Mobile              | SecureGuard® Client, Speco Blue                                |

### Interfaces

|           |                                     |
|-----------|-------------------------------------|
| Ethernet  | RJ45 Jack, 10/100 Mbps, PoE         |
| Power     | 12VDC input jack                    |
| Audio     | Built-in speaker, 3.5mm input       |
| Card slot | MicroSD, up to 256GB (not included) |
| Alarm     | 1ch alarm in, 1ch alarm out         |
| Reset     | Yes                                 |

### Network Specifications

|              |   |
|--------------|---|
| Protocols    | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS |
| DDNS support | Speco DDNS (free of charge)   |
| Security     | User ID & Password protection, IP/MAC address filtering, digest authentication            |
| User Access  | Max. 10 simultaneous users<br>Actual number of users may vary depending on bandwidth      |

### Other Specifications

|                |  |
|----------------|--|
| PoE            | Standard (IEEE 802.3af)  |
| Analytics      | Motion detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection. |
| Alarm Triggers | Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection  |
| Alarm Events   | FTP upload, email upload   |
| Image Settings | Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction  |

### Audio Specifications

|                   |                  |
|-------------------|------------------|
| Audio Compression | G.711A / G.711U  |
| Audio Input       | 3.5mm input      |
| Audio Output      | Built-in speaker |

### Operating & Unit Specifications

|                       |  |
|-----------------------|--|
| Power                 | PoE, 12VDC (power supply not included) |
| Power Consumption     | 12.0W (max)                            |
| Operating Temperature | -40°F - 140°F                          |
| Operating Humidity    | less than 95% (non-condensing)         |
| Unit Dimensions       | 8.57" (L) x 3.17" (W) x 3.16" (H)      |
| Unit Weight           | 1.53 lb                                |
| Certifications        | FCC, ONVIF Profile T                   |




\*With compatible Speco Blue Recorder  
\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

### Optional Accessories



### Cameras Interfaces



ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 6/14/22