

5MP HD-TVI IR Dome Camera with Included Junction Box

V5D2



2.8mm Fixed Lens, White Housing

Features

- Supports up to 5MP @ 20FPS
- IR Distance: 65' (depending on scene reflection)
- DWDR

NDAA COMPLIANT

- 12VDC Operation (power supply not included)
- IP67 weather resistance
- IK10 vandal resistance
- NDAA Compliant* •
- 5 year warranty





Camera Specifications

Image Sensor	Progressive scan 1/2.7" CMOS
Resolution	5MP 2560x1936 AHD/TVI/CVI/CVBS (*camera comes defaulted to HD-TVI) Image System Auto; 1/50s-1/100000s(PAL);1/6 0s-1/100000s (NTSC) Color: 0.01lux @ F1.2(AGC ON); B/W: 0 lux @ IR ON
Video Output	
Image System	
Electronic Shutter Speed	
Minimum Illumination	
S/N Ratio	≥ 52dB (AGC OFF)
Function Control	OSD (UTC Control)
Day/Night	
WDR	V
DNR	\checkmark
Gain Control	Auto
White Balance	ATW
Defog	X
BLC	
LSC	\checkmark
Mirror	\checkmark
Sharpness	\checkmark
Smart IR	\checkmark
Image Setting	\checkmark
Defect Correction	✓ Auto
Angle Adjustment	Pan 0° ~ 355°, Tilt 0° ~ 67°, Ro- tation 0° ~ 180°

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF \leq 1W; IR ON \leq 4W
Operating Temperature	-22°F - 122°F
Relative Humidity	10% ~ 90%
Unit Dimensions	3.5"(H) x 4.7"(Dia.)
Unit Weight	2.13lbs

Optional Accessories





Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com

*Products are in compliance with NDAA Section 889 Part B Guidelines

