

## VLDT4G

3.6mm fixed lens, dark gray housing

## VLDT4W

3.6mm fixed lens, white housing



### Features

- 1/2.9" 2MP Sony CMOS
- Supports multiple video signal outputs (TVI / AHD / CVI / CVBS)\*
- 18 built-in IR LEDs
- IP66 compliant, weather resistant
- Full OSD operation through UTC (up the coax)
- Junction box included
- 5 year warranty



Camera Specifications	
Image Sensor	1/2.9" 2MP Sony CMOS
Maximum Resolution	1920x1080
Field of View	83° ± 3°
Minimum Illumination	0 lux
Number of IR LEDs	18
IR Distance	Up to 65 ft. (depending on scene reflection)
White Balance	ATW
Backlight Compensation	Auto
Electronic Shutter Speed	NTSC: 1/60-1/100,000 PAL: 1/50-1/100,000
AGC	On/Off
DNR	On/Off
WDR	On/Off
Day/Night	Auto / Color / BW / EXT
OSD	UTC
Gamma	0.45 typ.
Scanning System	Progressive
Video Signal Output	HD-TVI / AHD / CVI / CVBS

Operating Specifications	
Power Supply	12VDC (power supply not included)
Power Consumption	Max. 400mA
Operating Temperature	-22°F - 104°F
Storage Temperature	-22°F - 104°F
Unit Dimensions	3.7" (W) x 3.15" (H)
Unit Weight	11.64 oz.

## NDAA COMPLIANT

\* Products are in compliance with NDA Section 889 Part B Guidelines

### Optional Accessories



**TVIUTPPT**  
HD Video Transceiver  
with Pigtail (Balun)



**TVIUTP**  
HD Video  
Transceiver



**PSW5**  
12VDC  
Power Supply

\*Cameras are defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/16/21